

# FALL PROTECTION PAD

Tendering text for Fall Protection Pad 30 mm.  
(CFH 1.6 m)

## **MATERIALS AND PRODUCTS:**

### **Fall Protection Pad 30 mm:**

- PE foam mat latticed like "Fall Protection Pad 30 mm"
- Thickness: 30 mm.
- Colour: White.
- Material: PE foam.
- Hole size: 10x50 mm.
- Pins for installation: 15 cm compostable pins.
- Infill: Topdressing such as Boldmix from Solum A/S.
- Grass seeds: E.g. Barenbrug RPR Sport.

### **Hybrid grass:**

- Hybrid Grass mesh, e.g. Green Hybrid 22.
- Blades of grass: 100% polyethylene (PE) monofilament
- Colour: Natural grass green
- Blade height: 18 mm (+/- 10%).
- Blade weight: 730 g/m<sup>2</sup> (+/- 10%).
- Mesh hole size: 15x36 mm (+/- 10%).
- Mesh structure: SBR – Latex.
- Total weight: 1,510 g/m<sup>2</sup> (+/- 10%).



NORDICLAWN.COM



INFO@NORDICLAWN.COM



(+45) 28 70 19 61

# FALL PROTECTION PAD

Tendering text for Fall Protection Pad 30 mm.  
(CFH 1.6 m)

## EXECUTION

### Fall Protection Pad 30 mm.

- For a layer of 15 cm of good topsoil, level the existing soil to +/- 3 cm evenness along a 3 m straightedge. Roll the soil lightly with a grid roller until footsteps only leave a light footprint.
- Fall Protection Pad 30 mm. is rolled out over the area and fastened with pins every 40 cm along all edges.
- The mesh of Fall Protection Pad 30 mm is filled completely with topdressing.
- Grass seeds are sown and Green Hybrid 22 hybrid grass subsequently installed.
- Then follow the installation instructions for Green Hybrid products.

### Hybrid grass:

- Hybrid grass is installed on already established/sown lawns.
- As far as possible, make sure that the rolls are rolled out in the same direction so that the blades point in the same direction. The edges of the rolls should be cut off before fastening.
- The hybrid grass is fastened at the edges using bio pins
- of at least 15 cm in length. 1 pin every 40 cm along the edges.
- The hybrid grass should be tightened before final laying.
- The centre is fastened with bio pins of at least 15 cm in length.
- 6 pins per m<sup>2</sup> (distance approx. 40 x 40 cm). Rolls are joined using the supplied sewing thread.

(See also the installation instructions from the manufacturer)



NORDICLAWN.COM



INFO@NORDICLAWN.COM



(+45) 28 70 19 61

# FALL PROTECTION PAD

Tendering text for 2 x Fall Protection Pad 30 mm  
(CFH 2.7 m)

## **MATERIALS AND PRODUCTS:**

### **Fall Protection Pad 30 mm:**

- 2 layers of PE foam mat latticed, e.g. Fall Protection Pad 30 mm
- Thickness: 30 mm (total 60 mm).
- Colour: White.
- Material: PE foam.
- Hole size: 10x50 mm.
- Pins for installation: 15 cm compostable pins.
- Infill: Topdressing such as Boldmix from Solum A/S.
- Grass seeds: E.g. Barenbrug RPR Sport.

### **Hybrid grass:**

- Hybrid Grass mesh, e.g. Green Hybrid 22.
- Blades of grass: 100% polyethylene (PE) monofilament
- Colour: Natural grass green
- Blade height: 18 mm (+/- 10%).
- Blade weight: 730 g/m<sup>2</sup> (+/- 10%).
- Mesh hole size: 15x36 mm (+/- 10%).
- Mesh structure: SBR – Latex.
- Total weight: 1,510 g/m<sup>2</sup> (+/- 10%).



NORDICLAWN.COM



INFO@NORDICLAWN.COM



(+45) 28 70 19 61

# FALL PROTECTION PAD

## Tendering text for 2 x Fall Protection Pad 30 mm (CFH 2.7 m)

### EXECUTION

#### 2 x Fall Protection Pad 30 mm

- For a layer of 15 cm of good topsoil, level the existing soil to +/- 3 cm evenness along a 3 m straightedge.
- Roll the soil lightly with a grid roller until footsteps only leave a light footprint.
- Fall Protection Pad 30 mm. is rolled out over the area and fastened with pins every 40 cm along all edges.
- The mesh of Fall Protection Pad 30 mm is filled completely with topdressing.
- Now lay out the next layer of Fall Protection Pad 30 mm. Wherever possible, avoid positioning joints directly on top of each other. Fasten with pins as with the first layer. And again fill with topdressing.
- Grass seeds are sown and Green Hybrid 22 hybrid grass subsequently installed.
- Then follow the installation instructions for Green Hybrid products.

#### Hybrid grass:

- Hybrid grass is installed on already established/sown lawns.
- As far as possible, make sure that the rolls are rolled out in the same direction so that the blades point in the same direction. The edges of the rolls should be cut off before fastening.
- The hybrid grass is fastened at the edges using bio pins
- of at least 15 cm in length. 1 pin every 40 cm along the edges.
- The hybrid grass should be tightened before final laying.
- The centre is fastened with bio pins of at least 15 cm in length.
- 6 pins per m<sup>2</sup> (distance approx. 40 x 40 cm). Rolls are joined using the supplied sewing thread.

(See also the installation instructions from the manufacturer)



NORDICLAWN.COM



INFO@NORDICLAWN.COM



(+45) 28 70 19 61